



Code 130108

AUTOMATIC ELMENDORF TEAR TESTER

Determines the tearing resistance of various materials

Standards: ISO 2493, SCAN P29, DIN 53121, BS 3748, TAPPI T556, NFQ 03-048



PTA SPAIN

C/ Gurutzegi N° 16 Pol. Belartza 20018 SAN SEBASTIÁN (Guipúzcoa) - Spain

PTA FRANCE

14, rue Evariste Galois / ZAC les Ruires 38320 EYBENS - France

PTA ASIA

50 East Coast Road #02-73 Roxy Square 428769 SINGAPORE - Singapore



PAPER Testing Equipment

PAPER TESTING ASSOCIATION

Device description

The Elmendorf tear tester has been developed specially for the paper industry and is outstanding for simplicity of operation and high measurement accuracy. The exchangeable pendulum is equipped with a pneumatic sample clamp. The initiation and return of the pendulum, as well as sample cutting is completely automatic. The device is operated via an integrated touch screen, where the test method can be selected, specific settings can be adjusted, and, after the measurement, results and statistics can be displayed. Each pendulum is supplied with the appropriate control weight so that, with the help of the service program, it can easily be checked for functionality and balance.

Test description

Up to 16 samples (acc. to standard 4 samples), prepared with the sample punch, are laid one on top of another and placed in the sample holder. On the touch screen, the number of samples inserted is selected, these are allocated to a test series (MD/CD) and the start button is pressed. The samples are automatically clamped and cut with a blade. Then the pendulum is automatically initiated and tears the sample above the cut. The pendulum is slowed, returned automatically to the start position, and the destroyed samples are released.

The force required to tear the sample is displayed on the touch screen. If more than one run is carried out in MD and CD, these can be compared as statistics, and the results displayed.

Specifications

| | Changeable pendulum |
|---|---|
| | Pneumatic sample clamping |
| | Easy operation via the integrated touch screen |
| | Fully-automatic test sequence and pendulum return |
| П | Control weight for checking the pendulum |

PTA SPAIN

PTA FRANCE

PTA ASIA

C/ Gurutzegi N° 16 Pol. Belartza 20018 SAN SEBASTIÁN (Guipúzcoa) - Spain 14, rue Evariste Galois / ZAC les Ruires 38320 EYBENS - France 50 East Coast Road #02-73 Roxy Square 428769 SINGAPORE - Singapore